

MEHTA

FIRE SAFETY HOUSE

A HOUSE OF SAFETY PRODUCTS



WE ARE THE KEY TO YOUR SAFETY



HOSE REEL DRUM

FIRSTAID FIRE SWINGING HOSE RELL WITH NOZZLE

- (I) Type "A" Swinging (180° wall mounting)
- (Inozzle IS: 8090-1976
- (II) Hose Reel tubing Hydraulic Rubber Hose IS : 444 -1980
- (III) as per IS : 884/85.
- Approval ISI Marked from Bureau of Indian Standards



HOSE BOX

HOSE BOX

Available in MS & ABS Body. (18 Gauge) with Accessories
All Sizes available according to the requirement.



SPRINKLERS

PENDENT TYPE SPRINKLER

- Temperature Rating : 155°f/68°C
- Glass Bulb Colour : Red
- Thread Size : NPT/2" or R1/2"
- Max. Service Pressure : 175psi
- Glass Bulb Diameter (mm) : O5





HYDRANT VALVE

LENDING VALVE IS : 5290

Material Gun metal Grade LTB-2 & Stainless Steel
Size 36 mm, 52 mm, 38 mm dia
63 Female Single outlet type- "A" ISI
52 Female Single outlet type- "A"
38 Female Single outlet type- "A"
Performance Hydraulic Test: 21 Kgf/cm²
Test Water Test: water tightness 14 kgf/cm²
Approval ISI Market from Bureau of Indian Standards. (63mm)



BRANCH PIPE / NOZZLES

SHORT BRANCH PIPE NOZZLE IS : 903

Material Gun metal Grade LTB-2, Stainless Steel & Aluminum
Size 63 mm, 38mm dia
12 mm to 20 mm dia for IS1 marked
Performance Hydraulic Test j 21 Kgf/cm²
Test
Approval ISI Market from Bureau of Indian Standards. (63mm)



FIRE HOSE

FIRE HOSE (C.P / RRL) IS 8423 / 636

Material Canvas/Reinforced Rubber
Size 15Mtr, 22.5 Mtr,
Approval 30 Mo-IS 8423/IS 636



COUPLINGS & ADAPTORS

FIRE HOSE DELIVERY COUPLING IS :903

Material Gun metal Grade LTB-2, Stainless Steel & Aluminum
Size 63 mm, 52 mm, 38 mm dia
Performance Hydraulic Test: 21 Kgf/cm² Test
Test
Approval 1 Market from Bureau of Indian Standards. (63mm)



MANUAL CALL POINT (MS)

The manual call point is tough, durable & highly visible, alarm led/s is provided inside the call point to indicate the alarm condition.

FEATURES Available for flush or surface, counting.
Suitable for majority of conventional fire alarm system,

SPECIFICATION	Voltage	18-26 V.D.C.
	Alarm Current	30ma
	Weight	540 Gm
	Dimension (mm)	115X90X52
	Colour	Red
	Material Of Cons.	Ms



SOUNDER (MS)

The electronic sounder is designed for use within fire alarm systems, security systems and industrial signaling systems, it provides an audio warning which is suitable for place which needs audio indication.

FEATURES 24/12 volt dc operation
High sound output with low current consumption.

SPECIFICATION	Voltage	20-26 V.D.C.
	Alarm Current	180ma
	Weight	565 Gm
	Dimension (mm)	185 X 125 X 75
	Colour	Red
	Material Of Cons.	Ms



PHOTO ELECTRIC SMOKE DETECTOR MODEL

FEATURES Low profile design
Low current draw
Product Overview
Wide operating voltage 8 to 30V DC
1 Bi-colour LED detector status indicator
Automatic drift compensation
Remote alarm test feature
Easy Maintenance
Range of detect or bases available
Remote LED Option
Approved to EN 54 - 7:2000 (Amendment 1)

MEHTA FIRE SAFETY HOUSE

FIRE ALARM PANEL

BASIC FEATURES

Easy Installation, Operation & Maintenance.

STANDARD FEATURES

Complies to IS 2189:1999 and Tested by ERTL (N) & System Sensor.

2 x 16 character backlit LCD display.

Lamp test feature.

Complete with integral power supply and battery charger for sealed lead acid battery.

Potential free contacts for both fire and fault.

Switches to enable on board operation.

LCD and LED indication for open, short circuit, isolate, fire in each zone, maximum nos. Of detectors in each zone is 25.



TESTED BY : ERTN (N) & SYSTEM SENSOR

ELECTRICAL SPECIFIC RTIOHS

Operating Voltage	24 Volts DC.
Stand by Batteries	24 Volts DC (2X12 volt DC)
Power Supply	
Mains	220 volt AC, 50 Hz to the internal mains transformer. (± 10%)
Input	26 volt from internal mains transformers.
Output	24 volt DC; 12 volt DC. (Regulated)
Charging Voltage:	27.2 volts DC.
End of Line Resistor	4.7 K Ohm, One per zone

FLEXIBLE DROPLETS

Specifications

Inlet connection	Dn25, Male BSP or NPT thread
Outlet connection	1/2" or 3/4" Female NPT thread
Internal diameter	25mm or 28mm
Hose length	700mm (28"), 1000mm (40"), 1200mm (47"), 1500mm (59*), 1800 (71") and other lengths provided on request
Bar length	700mm (28"), 1000mm (40"), other lengths also available
Working pressure	175psi(12.1bar)





Upper
Inner Lining
Temperature resistance
Electrical Resistance
Size
Sole Type
Height

Direct Injection PVC
Breathable textile lining. 280 GSM
Maximum 150°C for 1 minute
Maximum 18 KV for 1 Minute exposure
5 to 11
Direct Injection Nitrilo-PVC sole
15to13incB^
Male



Electrical shock resistance, chemical oil fuel resistancesole and slip resistance.resistance < 150°C 1



FULL BODY HARNESS
AB-65 (1 No.)



FALL ARRESTER
AB 300 (1 NO.)



ANCHORAGE WEBBING SLING
AB-600 (50 Mtr.)



GRIP DESCENDER
AB 700 (1 No.)



KARABINER
AB 400 (1 No's)



KERNMANTLE ROPE
AB-602



ANCHORAGE ROPE
AB-600 (50 Mtr.)

UNIVERSAL KIT
BAG



TOO BAG
(1 No.)



- Main Features**
- Wrtfiout rubber base
 - Height 750mm
 - Square Base : 395 x 395mm
 - Weight: 1200gms (Approx)



- Main Features**
- Height: 750mm
 - Weight: 4300gms (approx)
 - Improve design heavy base.

- Made of High density Polymer.
- Triple corrugation for enhanced strength.
- Provided with slide slots for fitting face and hearing protection accessories.
- Adjustable chinstrap.
- Comes with manual adjustment to suit most head sizes.
- The head band is made of non-irritant and soft-fabric to provide maximum comfort to the user
- The four point attachment cradle within the shell has a unique angular placement to provide japurjum shock absorption.



- The ratchet adjustment can be set to the desired head size by turning the hand-wheel. The adjustment position is locked when the hand-wheel is released.
- The helmets are provided in vast range of colors which are stabilized against ultraviolet degradation through appropriate UV stabilizers.
- Colours: Red-200, Florescent Green, Hyd Green, Florescent Orange, Star Blue, lamination Blue, Super Whiter lemon Yellow, Mint Green, Chrome Orange Apex Grey and UT Violet





Fire Extinguisher



MEHTA FIRE SAFETY HOUSE

A HOUSE OF SAFETY PRODUCTS

Deals in : All Fire Fighting Equipments and all safety items

5-1-236/237/4, 1st Floor, Old Ghasmandi, Secunderabad-03

Ph : 040-66385090, 27712717, Cell : 8008867105, ~~XXXXXXXXXX~~

Email : salemehtasafety@gmail.com