



MHIL / MHI - BC

Horizontal twin pump booster
(SS impeller)

Technical Data:
Flow: upto 430 LPM
Head: upto 65 m

- Application:**
- Pressure boosting in
 - Bungalows
 - Farm houses
 - Apartments and
 - Hotels

WBO4 Tejas 100mm Oil Filled Wilo Borehole Pump

Technical Data:
Flow: upto 120 LPM
Head: upto 85 m
Power: upto 1.5HP
Voltage: 160 V to 240 V

- Application:**
- Domestic household water supply to high rise building, housing complex, villas, farm houses, gardens and nurseries
 - Washing – garages, poultry farms, cattle farms, and stud farms



FAS / FAC

De-watering pump

Technical Data:
Flow: upto 1700 LPM
Head: upto 30 m
Solid passage: upto 56 mm

- Application:**
- Dewatering from residential buildings
 - Commercial buildings
 - Industry
 - Hospitals



WBW 75 mm (3") PLUS

Water Filled
Borewell Submersible Pumpset
Available single & 3 phase

Technical Data:
Flow: upto 70 LPM
Head: upto 82 m
Power: upto 1 HP

- Application:**
- Domestic household water supply to high rise building, housing complex, villas, farm houses, gardens, nurseries and fountains
 - Washing – garages, poultry farms, cattle farms, and stud farms

WBW 125/150/175/200 mm (5/6/7/8") Water Filled Borewell Submersible Pumpset

Available single & 3 phase

Technical Data:
Flow: upto 2200 LPM
Head: upto 227 m
Power: upto 25 HP

- Application:**
- Domestic household water supply to high rise building, housing complex, villas, farm houses, gardens, nurseries and fountains
 - Washing – garages, poultry farms, cattle farms, and stud farms



STS/PDV/TC

Sewage pump

Technical Data:
Flow: upto 1500 LPM
Head: upto 32 m
Solid passage: upto 35 mm

- Application:**
- Sewage disposal from residential buildings
 - Commercial buildings
 - Industry
 - Small hospitals



WBW 100 mm (4") PLUS

Water Filled
Borewell Submersible Pumpset
Available single & 3 phase

Technical Data:
Flow: upto 500 LPM
Head: upto 348 m
Power: upto 5 HP

- Application:**
- Domestic household water supply to high rise building, housing complex, villas, farm houses, gardens, nurseries and fountains
 - Washing – garages, poultry farms, cattle farms, and stud farms

Wilo-Initial Drain & Waste Submersible (Polypropylene) Pump

Technical Data:
Flow: upto 235 LPM

Head: upto 8 mts
P2: upto 0.75 kW (1hp)
Voltage: 230 V
Phase: Single
Max. immersion depth: 5 m

- Application:**
- drainage of clear or slightly dirty water, for domestic use
 - lifting of waste water even with suspended solids, for domestic use



Rexa/MTC

Cutter pumpset

Technical Data:
Flow: upto 358 LPM
Head: upto 39 m
Power: upto 3.9 kW (5hp)
Voltage: 230 V / 400 V
Phase: Single / Three
Max. immersion depth: 20 m

- Application:**
Pumping of:
- Sewage containing faeces
 - Pre-cleaned sewage without faeces and long fibre components
 - Wastewater





WPM101 Royal/Wilo Crown
Self-priming mini pumpset, available in single phase only

Technical Data:
Flow: upto 83 LPM
Head: upto 20.46 m
Power: upto 420 Watt (1.5 HP)
Voltage: 240 V

Application:
Water transfer in:
→ Bungalows
→ Farm houses
→ Apartments
→ Industry Use



MPO
Horizontal Open well Submersible pumpset- 3 Phase

Technical Data:
Flow: upto 2250 LPM
Head: upto 78 m
Power: upto 30 HP
Voltage: available in 3 phase

Application:
Water transfer in:
→ Bungalows
→ Farm houses
→ Apartments
→ Agriculture



WJ1
Self-priming jet pump (SS body)

Technical Data:
Flow: upto 83 LPM
Head: upto 50 m
Available in single and three phase

Application:
→ Pumping water from wells
→ Filling, pumping empty, transferring by pumping, irrigation and sprinkling
→ As emergency pump for overflows farms.



MNC
Self-priming Non-Clog pump & pumpset

Technical Data:
Flow: upto 4446 LPM
Head: upto 36 m
Power: upto 26 HP
Voltage: 230 V (Single phase) 415 V (Three phase)

Application:
→ De-watering from trenches, pits, basements, godowns, multistory, shopping malls, hospitals, hotels
→ Sewage pumping, rain water, flooding and mud transfer



MPM
Monoblock pumpset- 3 Phase

Technical Data:
Flow: upto 2200 LPM
Head: upto 7.8 m
Power: upto 30 HP
Voltage: 230 V (Single phase) 415 V (Three phase)

Application:
Water transfer in:
→ Bungalows
→ Farm houses
→ Apartments
→ Curbing at construction Sites



Star RS 15/6, RS 25/6, RS 25/8
Hot water circulator

Technical Data:
Flow: upto 100 LPM
Head: upto 8 m

Application:
→ Solar System, Heat Pumps system
→ Industrial use
→ Cold water systems & air condition system



PB
Inline pressure booster

Technical Data:
Flow: upto 80 LPM
Head: upto 1.9 m
Power: upto 400 Watt
Available in 1 Ph

Application:
→ Pressure boosting water transfer from roof tank to tap
→ Silent operation



FWJ /HWJ
Single pump booster (SS Impeller)

Technical Data:
Flow: upto 80 LPM
Head: upto 46 m
Voltage: 1 - 230 V, 50 Hz.

Application:
Water transfer in
→ Bungalows/ farm houses
→ Apartments/ hostels



HMHL /FMHHL
Single pump booster (SS Impeller)

Technical Data:
Flow: upto 215 LPM
Head: upto 62 m
Voltage: 1 - 230 V, 50 Hz.

Application:
Water transfer in
→ Bungalows/ farm houses
→ Apartments/ hostels
→ Silent in Operation



WPO /WPO Maxima
Horizontal Open well submersible pumpset- single phase

Technical Data:
Flow: upto 740 LPM
Head: upto 33 m
Power: upto 3 HP
Voltage: 230 V

Application:
Water transfer in:
→ Bungalows
→ Farm houses
→ Apartments



PW
Peripheral inline booster

Technical Data:
Flow: 40 LPM
Head: 45 mts
Pipe Size: 25 mm

Application:
→ Boosting water pressure at taps and showers
→ Water supply for household use
→ Water transfer for small machines and instruments
→ Sprinkler systems
→ Gardening and car washing



TW15

Multistage Submersible pumpset

Technical Data:
Flow: upto 266 LPM
Head: upto 88 m
TW13 & TW15- 1 Ph & TW13- 1 Ph & 3 Ph

Application:
Pumping clear water from
→ Well
→ Rainwater storage tank vessels
→ Irrigation, sprinkling a pumping out clear water
→ Water supply
→ Rainwater utilisation